


GX75K V TWIN



Frequency	50 Hz
Voltage	415/240 V
Prime power	64 kVA
Standby power	70 kVA
Power factor	cos φ 0,8
Prime power	51,2 kWe
Standby Power	56 kWe
Fuel consumption 70% load	13,6 l/h



Engine x 2	KOHLER KDI 1903TCR CAC	Alternator x 2	LEROY-SOMER LSA 42.3 VS3
Prime power	31 kWm	Continuous power	32 kVA
Cylinders	3	Protection	IP 23
Displacement	1.861 cm³	Voltage regulation	± 0,25%
Emissions		Short-circuit current	300% : 10s - AREP

Control panel x 2	Q8610S	Dimensions	300 x 190 x 190 cm L x W x H
Electronic control module	DSE 8610 MKII	Total dry weight	3.500 kg
Load sharing control panel	Remote start on load Remote start on load demand	Total wet weight	4.000 kg

Standard features	Options
<ul style="list-style-type: none"> Central lifting point Forklift pockets 600 litres bunded fuel tank VELCB with ON/OFF switch Hardwire copper busbar with microswitch protection Sump oil vacuum pump Battery isolator 	<ul style="list-style-type: none"> Divertor valve Battery charger Engine block heater Sockets kit Powerlocks Bund alarm RACOR filter